

PIK KEMICAL

Chemical Technologies

C/3

FILTER CLEANER

LIQUID CLEANING AGENT FOR REMOVAL FROM FILTERS OF CARBONIZED OIL RESIDUES

Technical Support:
pikkemical@pikkemical.it

Orders-Enquires:
pikkemical@pikkemical.it

Ph. +39 0586940120

DESCRIPTION

Aliphatic and aromatic hydrocarbons mixed with anionic surface-active agents.

- Removes carbonised oil, wax and paraffin.
- Designed for oil and fuel filters.
- Not corrosive product.

APPLICATIONS

FILTER CLEANER is mainly used for cleaning any type of metal or ceramic filters.

INSTRUCTIONS

Use FILTER CLEANER pure, in a tank, heating up to max. 60°C, dipping the dirty engine parts. Or apply directly circulating in the heat exchangers. The circulation time depends on the actual status of the heat exchangers and is, in any case, between 8 and 24 hours.

PRECAUTIONS

While applying this treatment keep the room vented.

Keep away from open fires.

Use gloves and protective glasses. Do not inhale vapours. In case of contact with the eyes rinse thoroughly with fresh running water and seek medical assistance.

PACKAGING

Non returnable

- Metallic drums 25 liters
- Metallic drums 208 liters