

PIK KEMICAL

Chemical Technologies

G/6

FULL

ANTIFREEZE FOR COOLING WATER SYSTEMS

Technical Support:
pikkemical@pikkemical.it

Orders-Enquires:
pikkemical@pikkemical.it

Ph. +39 0586940120

DESCRIPTION

Antifreeze and anticorrosive liquid for cooling water systems. FULL is compatible with all nitrite and phosphonate products. Must be used diluted. Dilution percentage depends on the temperatures of the system to be protected.

INSTRUCTIONS

For the quantity required please refer to the table

PRECAUTIONS

This product is not toxic nor dangerous

PACKAGING

Not returnable
- Plastic pails 25 liters

DOSAGE AND CHARACTERISTICS OF ANTIFREEZE IN AQUEOUS SOLUTION

Weight %	Volume %	Spec. Gravity at 20 °C	Freezing point °C	Boiling point °C
0	0.0	1.000	0	100.0
10	9.1	1.013	-3.5	101.1
20	18.4	1.027	-8	102.2
30	28.0	1.040	-15	103.3
40	37.8	1.057	-24	104.9
50	47.8	1.067	-36	107.2
60	58.0	1.079	-50	109.9
70	68.4	1.090	-49	114.4
80	78.9	1.100	-47	122.2
90	89.4	1.108	-29	137.2
100	100.0	1.115	-13	197.2