

PIK KEMICAL

Chemical Technologies

S/6

biofresh plus powder

POLIVALENT BIOLOGICAL ACTIVATOR FOR DIGESTION OF ORGANIC SUBSTANCES

Technical Support/ Supporto Tecnico:

pikkemical@pikkemical.it

Orders-Enquires/Ordini-Richieste di offerta:

pikkemical@pikkemical.it

Ph. +39 0586940120

DESCRIPTION

BIOFRESH PLUS is a balanced compound composed of bacteria, enzymes and nutritious elements that become active on fat, food leftovers, paper and organic matter causing foul odors.

APPLICATIONS

BIOFRESH PLUS is designed for use in sanitary installations, kitchen drains, eating areas, waste water of food industry, slaughter houses, drains, grease traps, septic tanks, grease separation tanks, water treatment plants, etc.

ADVANTAGES

BIOFRESH PLUS action permits the digestion of above mentioned substances with following advantages:

Elimination of vegetal and animal fat, digestion of proteins, and amides, thus suppressing foul odors and preventing clogging of drains.

Regeneration of bacterial flora in septic tanks resuming the COD (Oxygen Demand), prevention of growth in the water as the bacteria contained in BIOFRESH PLUS feed on phosphates.

BIOFRESH PLUS is a natural product without any harmful effect on the environment.

BIOFRESH PLUS is a highly concentrated powder containing approximately 420 million free bacteria per gram that can operate either in aerobic or anaerobic mode, i.e. with or without oxygen.

INSTRUCTIONS

FLUSH TANKS:

First, second and third weeks:

100 grams of product per day for each 100 MT of discharge or per cubic meter of flush water to be treated.

Maintenance and odor removing:

200 grams per day for each 100 MT of discharge or per cubic meter of flush water to be treated (twice a week).

SEPTIC TANKS:

First, second and third weeks:

100 -150 grams of product per day per cubic meter of capacity.

Maintenance and odor removing:

50 -100 grams of product per cubic meter capacity twice a week.

It is recommended to use BIOFRESH PLUS when the discharge is inactive.

Pour the product in the installation after dissolving the powder in lukewarm water at the rate of approx. 10% concentration (100 grams of product in 1-2 liter of water). Ensure that there is enough slant in drainpipes to guarantee proper flow of the product in the drains leading to the tank.

PRECAUTIONS

Store in cool and dry place at temperatures between 10 and 45°C.

Close containers tightly after use.

Do not use together with acids, alkali, bleach or disinfectants. Wash hands after manipulating the product (as a simple precaution). Keep away from children.

PACKAGING

- Carton 12 pieces of 1 Kg each